


DETECTABLE WARNING  
PATTERN AREA SHALL BE  
YELLOW IN COMPLIANCE  
WITH WSDOT STD. SPEC. 8-14.3(3)



**ELEVATION**  
TRUNCATED DOMES (SEE NOTE 3)

	MIN.	MAX.
A	1 5/8"	2 3/8"
B	5/8"	1 1/2"
C	7/16"	3/4"
D	7/8"	1 7/16"

**NOTES:**

1. INSTALL WHEELCHAIR RAMP AS LOCATED ON APPROVED PLANS OR AS DIRECTED BY THE TRAFFIC ENGINEER.
2. SEE SD310B FOR CURB RAMP LAYOUT.
3. DETECTABLE WARNING PATTERNS MAY BE CREATED BY METHODS THAT WILL ACHIEVE THE TRUNCATED DOME DIMENSIONS, COLOR AND SPACING SHOWN AS DIRECTED BY THE PLANS OR TRAFFIC ENGINEER.

**DETECTABLE WARNING  
PATTERN DETAIL**

**SIDEWALK RAMP TYPE 2**

TYPICALLY USED WHEN SIDEWALK AREA BEHIND RAMP IS LESS THAN 4' MIN.

NO SCALE

APPROVED: **DON CAIRNS**

REV. DATE: **NOVEMBER 01, 2005**

TRANSPORTATION DIVISION



**STANDARD DETAILS**

**SIDEWALK RAMP TYPE 2**

FILE	<b>SD310A</b>	DRAWING NO.	<b>310A</b>
------	---------------	-------------	-------------